

MEDIUM TRUCK



H-703

- Open shoulder drive axle rib
- Aggressive tread blocks yield strong resistance to puncture
- 4 belts
- Slim sipes give excellent heat dissipation, better wet surface grip and anti-skid properties



Item	Tire Size, Load Range, & Service Description	PR	Ship Weight (lbs.)	Meas. Rim Width (inches)	Tread Depth (32 ^{nds})	Dual Max. Load	Dual Max. PSI	Single Max. Load	Single Max. PSI	Section Width	Overall Diameter	Min Dual Spacing	Eclipse Code
------	--	----	--------------------------	--------------------------------	--	----------------------	---------------------	------------------------	-----------------------	------------------	---------------------	---------------------	-----------------

H-703

59970	11R22.5	BLK	146/143L	16	123	8.25	26	6005	120	6610	120	10.94	41.81	12.52	59970
59540	295/75R22.5	BLK	144/141L	14	120	8.25	26	5675	110	6175	110	10.83	40.47	12.52	59540
59974	11R24.5	BLK	149/146L	16	132	8.25	26	6610	120	7160	120	10.94	43.86	12.52	59974
59539	285/75R24.5	BLK	144/141L	14	117	8.25	26	5675	110	6175	110	10.83	41.85	12.52	59539
59537	11R22.5	BLK	144/142L	14	126	8.25	26	5842	104	6173	104	10.94	41.81	12.52	59537
59538	11R24.5	BLK	146/143L	14	135	8.25	26	6008	104	6614	104	10.94	43.86	12.52	59538