



GF/RF 766

- Wheel position : Steer axle or trailers
- For highway and improved road surfaces
- Good anti-sideslip and anti-abnormal wear resistance performance
- Low rolling resistance performance
- Low heating-making
- Superior high-speed performance

Product Number	Tire Size	Pattern	PR	Rim Size	Tread Depth (mm)	Load Index S/D & Speed S	Section Width (mm)	Overall Diameter Hwy/Traction (mm)	Max. Air Single/Dual (kpa)	Load Capacity Single/Dual (kg's)	Qty/40'HC	Price (USD)
63916	11R22.5	GF766	14	8.25	15	144/142 & M	279	1054	720/720	2800/2650		
63917	11R22.5	GF766	16	8.25	15	146/143 & M	279	1054	830/830	3000/2725		
63976	11R24.5	GF766	14	8.25	15	146/143 & M	279	1104	720/720	3000/2725		
63979	11R24.5	GF766	16	8.25	15	149/146 & M	279	1104	830/830	3250/3000		
63912	12R22.5	GF766	18	9.00	15.5	152/149 & M	300	1085	930/930	3550/3250		
63995	295/75R22.5	GF766	14	9.00	15.5	144/141 & M	298	1014	760/760	2800/2575		
63908	295/80R22.5	GF766	16	9.00	15.5	150/147 & M	298	1044	830/830	3350/3075		
63910	295/80R22.5	GF766	18	9.00	15.5	152/149 & M	298	1044	900/900	3550/3250		